

# Chem Link Products Reduce VOC's and Add Value to Green Construction Projects

Product	V.O.C. content ASTM D 2369	LEED Credits (USGBC) Low-Emitting Materials Section 4.1	NAHB Green Home Building Guidelines Global Impact Credits Section 7.1.3	CARB Sealant <4% VOC	SCAQMD Adhesive / Sealant < 250 g/L
<b>M-1</b>	19.63 g/l VOC 1.4%	1 pt EQ credit	5 pts	Exceeds Requirement	Exceeds Requirement
<b>NovaLink</b>	18.26 g/l VOC 1.2%	1 pt EQ credit	5 pts	Exceeds Requirement	Exceeds Requirement
<b>NovaLink SL</b>	14.93 g/l VOC 1.4%	1 pt EQ credit	5 pts	Exceeds Requirement	Exceeds Requirement
<b>Mean Green</b>	31.97 g/l VOC 2.3%	1 pt EQ credit*	5 pts	Exceeds Requirement	Exceeds Requirement
<b>DuraLink</b>	18.29 g/l VOC 1.4%	1 pt EQ credit	5 pts	Exceeds Requirement	Exceeds Requirement
<b>Clear</b>	13.40 g/l VOC 1.3%	1 pt EQ credit	5 pts	Exceeds Requirement	Exceeds Requirement
<b>DuraSil</b>	32.86 g/l VOC 3.3%	1 pt EQ credit*	5 pts	Exceeds Requirement	Exceeds Requirement
<b>Roof Assembly Adhesive</b>	43.31 g/l VOC 2.6%	1 pt EQ credit*	5 pts	Exceeds Requirement	Exceeds Requirement
<b>MetaLink</b>	12.39 g/l VOC 1.2%	1 pt EQ credit*	5 pts	Exceeds Requirement	Exceeds Requirement
<b>BARR FP</b>	42.26 g/l VOC 3.04%	1 pt EQ credit	5 pts	Exceeds Requirement	Exceeds Requirement

## LEED VOC requirements:

- Multipurpose construction adhesives 70g/Liter
- Architectural Sealants 250g/Liter
- Ceramic Tile Adhesives 65 g/Liter
- Wood & Metal to Metal 30 g/Liter

## Additional environmentally friendly properties of Chem Link products:

- All of the above Chem Link products contain no solvent
- There are no isocyanates (TDI or MDI) in any of the above Chem Link products
- Chem Link products are SCAQMD, CARB, and FDA compliant

\* Meets LEED requirements for Low Emitting materials in almost all applications and substrates.